

LIST TEAMS

Overview

Retrieve all **teams**, ordered by the highest rank.

Request URL

All parameters in the request must be sent as a `POST` HTTP request.
Make all requests to the following URL:

```
1 | https://leaderboards.construct.net/listteams.json
```

Authenticating The Request

No authentication is required for calling this end point.

secret string **Optional**

Your games **secret API key**.

Request Parameters

gameID guid **Required**

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS) account**.

leaderboardID guid **Required**

The ID of the leaderboard you're fetching teams from.

order string

How you wish the teams returned in this query to be ordered. Can be one of **BestRanked**, **WorstRanked**, **NameAZ**, **NameZA**, **MostPlayers**, **LeastPlayers**, **Newest** or **Oldest**. The default value if not specified is **Newest**.

perPage int32

How many teams you wish to return on each page of results. Cannot be less than **1** or more than **100**. Default value is **20**.

page int32

The page of results you are requesting. The first page is always **1**. If this value is not specified the first page will be returned.

culture string **Optional**

Optionally specify a **supported culture code** for rendering various properties. If not specified, the culture code from your games default language will be used.

Success Response

Successful responses always return a **HTTP 200** status code.

```
1  {
2    "success": true,
3    "pagination": { ... },
4    "teams": [
5      { ... },
6      { ... }
7    ],
8    "formattingCulture": "en-us"
9  }
```

Response Properties

success **bool**

If the request was successfull or not.

pagination **Pagination**

A pagination object helpful for navigating other pages of results.

teams Array<ExpandedTeam>

The list of team objects returned from the request.

formattingCulture string

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return **HTTP 4xx** status codes.

```
1 {  
2   "success": false,  
3   "errorMessage": "Your request failed due to...",  
4   "helpURL": "https://www.construct.net/en/game-services/manuals/gam  
5   "shouldRetry": false  
6 }
```

Response Properties

success bool

If the request was successful or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.

You are here:

Search this manual:



[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 9 Mar, 2026 at 15:59