

CREATE A BONUS

Overview

This end point allows you to create a new **XP bonus period**.

Request URL

All parameters in the request must be sent as a `post` HTTP request.
Make all requests to the following URL:

```
1 | https://xp.construct.net/createbonus.json
```

Authenticating The Request

This end point is for **secret key** authenticated requests only. Signed in players cannot call this end point.

secret `string` **Required**

Your games **secret API key**.

Request Parameters

gameID `guid` **Required**

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS) account**.

start `int64` **Required**

The datetime the bonus will start as a unix time stamp (seconds since Jan 01 1970).

end int64 **Required**

The datetime the bonus will end as a unix time stamp (seconds since Jan 01 1970).

modifier string **Required**

The bonus multiplier. Must be a value between **1.1** and **100**

title string

A title for the bonus which may be shown to the end users.

description string

A description for the bonus which may be shown to the end users.

language string

Provide this parameter to set the language that the title and description are written in. Permitted values are **AR**, **BG**, **CS**, **DA**, **DE**, **EL**, **EN**, **ES**, **ET**, **FI**, **FR**, **HE**, **HU**, **ID**, **IT**, **JA**, **KO**, **LT**, **LV**, **NB**, **NL**, **PL**, **PT**, **RO**, **RU**, **SK**, **SL**, **SV**, **TH**, **TR**, **UK**, **VI**, **ZH**. If not specified, your games default language will be used.

culture string **Optional**

Optionally specify a **supported culture code** for rendering various properties. If not specified, the culture code from your games default language will be used.

Success Response

Successful responses always return a **HTTP 200** status code.

```
1 {  
2   "success": true,  
3   "bonus": { ... },  
4   "formattingCulture": "en-us"  
5 }
```

Response Properties

success **bool**

If the request was successfull or not.

bonus XPBonus

An XP bonus object.

formattingCulture string

If some return values are culture specific, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return HTTP 4xx status codes.

```
1 | {  
2 |   "success": false,  
3 |   "errorMessage": "Your request failed due to...",  
4 |   "helpURL": "https://www.construct.net/en/game-services/manuals/game-s  
5 |   "shouldRetry": false  
6 | }
```

Response Properties

success bool

If the request was successfull or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.

Search this manual:

Community Help

Contact Us

This manual entry was last updated on 26 Feb, 2026 at 15:19