

LIST BONUSES

Overview

This end point allows you to list **XP bonuses** that run or have run between the specified dates. Returned bonuses are ordered by soonest first. You cannot search periods longer than **366** days, or periods further than **5** years ahead of time..

Request URL

All parameters in the request must be sent as a **POST** HTTP request. Make all requests to the following URL:

```
1 | https://xp.construct.net/listbonuses.json
```

Authenticating The Request

No authentication is required for this request type.

Request Parameters

gameID **guid** **Required**

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS) account**.

end **int64** **Required**

The end date and time bonuses to search until as a unix time stamp (seconds since Jan 01 1970).

start int64

The start date and time bonuses to search from as a unix time stamp (seconds since Jan 01 1970). If not specified, the requests date and time will be used.

culture string **Optional**

Optionally specify a **supported culture code** for rendering various properties. If not specified, the culture code from your games default language will be used.

Success Response

Successful responses always return a **HTTP 200** status code.

```
1 {  
2   "success": true,  
3   "bonuses": [  
4     { ... },  
5     { ... }  
6   ],  
7   "formattingCulture": "en-us"  
8 }
```

Response Properties

success bool

If the request was successfull or not.

bonuses Array<XPBonus>

All bonuses returned in the request.

formattingCulture string

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return **HTTP 4xx** status codes.

```
1 | {  
2 |   "success": false,  
3 |   "errorMessage": "Your request failed due to...",  
4 |   "helpURL": "https://www.construct.net/en/game-services/manuals/game  
5 |   "shouldRetry": false  
6 | }
```

Response Properties

success bool

If the request was successful or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 4 Mar, 2026 at 15:24