

EDIT A RANK

Overview

This end point allows you to edit an existing **XP rank**. Only specify the properties in the request you wish to update.

Request URL

All parameters in the request must be sent as a **POST** HTTP request. Make all requests to the following URL:

```
1 | https://xp.construct.net/editrank.json
```

Authenticating The Request

This end point is for **secret key** authenticated requests only. Signed in players cannot call this end point.

secret string **Required**

Your games **secret API key**.

Request Parameters

gameID guid **Required**

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS) account**.

rankID guid **Required**

The ID of the rank you're editing.

xp int64

The XP level required to achieve this rank.

title string

A title for the rank which may be shown to the end users.

description string

A description for the rank which may be shown to the end users.

language string

Provide this parameter to set the language that the title and description are written in. Permitted values are **AR**, **BG**, **CS**, **DA**, **DE**, **EL**, **EN**, **ES**, **ET**, **FI**, **FR**, **HE**, **HU**, **ID**, **IT**, **JA**, **KO**, **LT**, **LV**, **NB**, **NL**, **PL**, **PT**, **RO**, **RU**, **SK**, **SL**, **SV**, **TH**, **TR**, **UK**, **VI**, **ZH**.

culture string **Optional**

Optionally specify a **supported culture code** for rendering various properties. If not specified, the culture code from your games default language will be used.

Success Response

Successful responses always return a **HTTP 200** status code.

```
1 {  
2   "success": true,  
3   "rank": { ... },  
4   "formattingCulture": "en-us"  
5 }
```

Response Properties

success **bool**

If the request was successful or not.

rank **XPRank**

An XP rank object.

formattingCulture string

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return **HTTP 4xx** status codes.

```
1 | {  
2 |   "success": false,  
3 |   "errorMessage": "Your request failed due to...",  
4 |   "helpURL": "https://www.construct.net/en/game-services/manuals/game  
5 |   "shouldRetry": false  
6 | }
```

Response Properties

success bool

If the request was successfull or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 4 Mar, 2026 at 15:24