

GET XP

Overview

Returns a players current XP, along with a rank if one exists.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
1 | https://xp.construct.net/get.json
```

Authenticating The Request

This end point can be called by `signed in` players, or with `secret key` authentication.

Session Key Authentication

`sessionKey` string **Required**

The `session key` of the player you're making the request against.

Secret Key Authentication

`secret` string **Required**

Your games `secret API key`.

`playerID` guid **Required**

The player ID you wish to make this request against.

Request Parameters

gameID guid **Required**

The ID of the game you are making this request against. You can find the ID of your game in your [Construct Game Services \(CGS\) account](#).

culture string **Optional**

Optionally specify a [supported culture code](#) for rendering various properties. If not specified, the culture code from your games default language will be used.

Success Response

Successful responses always return a `HTTP 200` status code.

```
1  {
2    "success": true,
3    "xp": 20674,
4    "formattedXP": "20,674",
5    "rank": { ... },
6    "nextRank": { ... },
7    "formattingCulture": "en-us",
8    "leaderboardScoreID": 20674
9  }
```

Response Properties

success bool

If the request was successful or not.

xp int64

This players current XP.

formattedXP string

This players current XP formatted to the requested formatting culture, formatted to the specified [requested culture](#).

rank XPRank

This players current XP rank if one exists.

nextRank XPRank

The next rank this player will unlock.

formattingCulture string

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

leaderboardScoreID guid?

This players current XP.

Failure Response

Unsuccessful responses always return **HTTP 4xx** status codes.

```
1 | {  
2 |   "success": false,  
3 |   "errorMessage": "Your request failed due to...",  
4 |   "helpURL": "https://www.construct.net/en/game-services/manuals/  
5 |   "shouldRetry": false  
6 | }
```

Response Properties

success bool

If the request was successfull or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 12 Mar, 2026 at 15:14