

FLASH BEHAVIOR SCRIPT INTERFACE

The `IFlashBehaviorInstance` interface derives from `IBehaviorInstance` to add APIs specific to the **Flash behavior**.

Example

Below is a sample code snippet demonstrating flashing `inst` (assumed to be an instance with the Flash behavior) and logging to the console when the flash finishes.

```
1 // Handle "flashend" event which logs to console when
2 // the flash has finished
3 inst.behaviors.Flash.addEventListener("flashend", e =>
4 {
5     console.log("Flash finished!");
6 });
7
8 // Start flashing with the Flash behavior for 2 seconds
9 inst.behaviors.Flash.flash(0.1, 0.1, 2);
```

Flash behavior events

See **behavior instance event** for standard behavior instance event object properties.

"flashend"

Fired when a flash finishes.

Flash behavior APIs

`flash(onTime, offTime, duration)`

Start flashing for the given **duration** with the object shown visible for the **onTime** and invisible for the **offTime**, with all times in seconds.

stop()

Stop any currently active flash effect, returning the object to a visible state.

isFlashing

A read-only boolean indicating if the object is currently flashing.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 2 Dec, 2022 at 12:08