

TWEEN SCRIPT INTERFACE

The `ITweenState` interface represents an actively running tween. It derives from `ITimelineStateBase` which implements APIs in common between timelines and tweens, as a tween is a kind of temporary timeline. Many general playback APIs are part of `ITimelineStateBase`; the `ITweenState` interface only provides APIs specific to tweens that do not also apply to timelines.

Tweens can be created using the `startTween()` method on the [Tween behavior script interface](#).



Once a tween is released, this interface is destroyed and all its properties will throw exceptions upon access. The only exception to this is the `isReleased` property (inherited from `ITimelineState`) which provides a read-only boolean that indicates if the interface has been released and is now invalid.

Tween APIs

`stop()`

Stops playback and immediately ends the tween. The interface is released in this call and so it cannot be used any further after this call.

`instance`

A read-only property with a reference to the [IWorldInstance](#) the tween is running on.

`isDestroyOnComplete`

Set or get a boolean indicating whether the corresponding instance will be automatically destroyed once the tween finishes.

value

A read-only number providing the current value of a value tween.

setEase(easeName)

Set the ease function used for the tween by a string of its name. Refer to the Tween behavior script interface for a list of valid built-in ease names, or use the name of a custom ease.

released

A promise that resolves when the tween is destroyed. Afterwards the rest of the API can no longer be used except for **isReleased** property (inherited from **ITimelineState**) which provides a read-only boolean that indicates if the interface has been released and is now invalid.

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 12 Mar, 2026 at 10:46