

LIST SCRIPT INTERFACE

The `IListInstance` interface derives from `IDOMInstance` to add APIs specific to the [List plugin](#).

List events

See [instance event](#) for standard instance event object properties.

"click"

Fired when the list is clicked.

"dblclick"

Fired when the list is double-clicked.

"selectionchange"

Fired when there is any change to the selected item or items.

List APIs

`addItem(text)`

Append a new item with the given text to the end of the list.

`insertItem(index, text)`

Insert a new item at a zero-based index in the list with the given text.

`setItemText(index, text)`

Set the item text at a zero-based index in the list.

getItemText(index)

Return a string of the current item text at a zero-based index in the list.

removeItem(index)

Delete an item at a zero-based index from the list.

clear()

Remove all items from the list, leaving the list empty.

itemCount

A read-only number representing how many items are in the list.

selectedIndex

Set or get a number indicating the zero-based index of the currently-selected list item.

selectedCount

A read-only number with the number of selected items. This is usually only useful with multi-select lists.

getSelectedIndexAt(index)

getSelectedTextAt(index)

Return the item index or the item text of a selected item by its index up to **selectedCount**. This is usually only useful with multi-select lists.

tooltip

A tooltip that appears if the user hovers the mouse over the list and waits. An empty string indicates no tooltip.

You are here:

Search this manual:

This manual entry was last updated on 3 Nov, 2022 at 12:15