

MOUSE SCRIPT INTERFACE

The `IMouseObjectType` interface derives from `IObjectClass` to add APIs specific to the [Mouse plugin](#).

Note this class derives from the object class interface, not the instance interface. Typically it is used through `runtime.mouse` instead of the named object.

Examples

The [Shooting code example](#) demonstrates pointing the player at the mouse cursor and shooting bullets towards it.

The [Tracking pointers](#) example also demonstrates how both mouse and touch input can be tracked simultaneously using pointer events.

Events

To detect mouse button events, use the events fired on the [Runtime script interface](#), such as `"mousedown"` Or `"pointerdown"`.

Mouse APIs

```
getMouseX(layerNameOrIndex)
getMouseY(layerNameOrIndex)
getMousePosition(layerNameOrIndex)
```

Return the current position of the mouse cursor on a layer, given by a case-insensitive string of its name or zero-based index. The parameter can be omitted for the default mouse position, which does not take in to account any specific layer's transformations. `getMousePosition()` returns both the X and Y position as `[x, y]`.

isMouseButtonDown(button)

Return a boolean indicating if the given mouse button is currently down. The button is specified the same way as the [MouseEvent.button](#) property, i.e. 0 for left, 1 for middle, and 2 for right.

setCursorStyle(style)

Set the appearance of the mouse cursor to a string of a CSS `cursor` style value, e.g. `"crosshair"`. See [cursor styles on MDN](#) for some possible values.

setCursorObjectClass(objectClass)

Set the appearance of the mouse cursor to the current image of an [ObjectClass](#). Various limitations apply: the object image is used as it appears in the image editor, not taking in to account size or rotation in the layout; the image cannot be too large (64x64 is usually the limit); the cursor may not be applied close to the edges of the browser window; and support varies depending on browser and OS. Some sample code for this method is shown below.

```
1 | runtime.mouse.setCursorObjectClass(runtime.objects.Sprite);
```

You are here:

Search this manual:

[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 16 Feb, 2024 at 14:33