

TILED BACKGROUND SCRIPT INTERFACE

The `ITiledBackgroundInstance` interface derives from `IWorldInstance` to add APIs specific to the **Tiled Background plugin**.

Tiled Background APIs

`imageWidth`
`imageHeight`
`getImageSize()`

The original dimensions of the Tiled Background's current image in pixels. This does not include tiling - it returns the size as shown in Construct's image editor. The method allows retrieving both values at the same time.

`imageOffsetX`
`imageOffsetY`
`setImageOffset(imageOffsetX, imageOffsetY)`
`getImageOffset()`

The offset of the displayed Tiled Background image in pixels. The methods allow setting or getting both values at the same time.

`imageScaleX`
`imageScaleY`
`setImageScale(imageScaleX, imageScaleY)`
`getImageScale()`

The scale of the displayed Tiled Background image, defaulting to 1 for original size. The methods allow setting or getting both values at the same time.

imageAngle

The angle of the displayed Tiled Background image in radians. If this is changed, **imageAngleDegrees** updates accordingly.

imageAngleDegrees

The angle of the displayed Tiled Background image in degrees. If this is changed, **imageAngle** updates accordingly.

enableTileRandomization

A boolean indicating whether tile randomization is enabled.

tileXRandom

tileYRandom

setTileRandom(tileXRandom, tileYRandom)

getTileRandom()

When tile randomization is enabled, the amount of random horizontal and vertical offset to use, as a percentage in the range 0-1. The methods allow setting or getting both values at the same time.

tileAngleRandom

When tile randomization is enabled, the amount of random rotation to use, as a percentage in the range 0-1.

tileBlendMarginX

tileBlendMarginY

setTileBlendMargin(tileBlendMarginX, tileBlendMarginY)

getTileBlendMargin()

When tile randomization is enabled, the percentage of the tile width or height which will fade in to the adjacent tile, as a percentage in the range 0-1. The methods allow setting or getting both values at the same time.

async replaceImage(blob)

Replace the current image with the contents of a **Blob** representing an image file such as a PNG image. The blob can be locally generated or retrieved from a URL, for example:

```
1 // Loading an image from a URL
2 const response = await fetch(url);
```

```
3 | const blob = await response.blob();  
4 | await tbInst.replaceImage(blob);
```

You are here:

Search this manual:



[Community Help](#)

[Contact Us](#)

This manual entry was last updated on 13 Jul, 2023 at 13:48