

DELETE PLAYER AVATAR

View online: <https://www.construct.net/en/game-services/manuals/game-services/authentication/api-end-points/avatars/delete-avatar>

Overview

Use this end point to delete a players avatar if they have one set. If this is called and the player doesn't have an avatar, it will still return a success response. Failure responses should only be returned if authentication fails, or there is a network error.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://auth.construct.net/deleteavatar.json
```

Authenticating The Request

This end point can be called by **signed in** players, or with **secret key** authentication.

Session Key Authentication

sessionKey string Required

The **session key** of the player you're making the request against.

Secret Key Authentication

secret string Required

Your games **secret API key**.

playerID guid Required

The player ID you wish to make this request against.

Request Parameters

gameID guid Required

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS) account**.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "formattingCulture": "en-us"
}
```

Response Properties

success `bool`

If the request was successful or not.

formattingCulture `string`

If some return values are `culture specific`, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/authentication/ap",
  "shouldRetry": false
}
```

Response Properties

success `bool`

If the request was successful or not.

errorMessage `string`

An error message with more detailed information on why the request failed.

helpURL `url (string)`

A link to documentation which should provide help with the error.

shouldRetry `bool`

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.