

LINK LOGIN PROVIDER

View online: <https://www.construct.net/en/game-services/manuals/game-services/authentication/api-end-points/login-providers/link-login-provider>

Overview

If a player is signed in, you can link another **login provider** to this player which gives them more ways to **sign-in** to their account. Only one account per provider is permitted for player accounts - for example you can't tie multiple Steam accounts to the same player account.

The provider `UsernamePassword` is not supported for link requests. Use the **set username password** end point instead to set a new username/password or update the users username/password.

When you request a link, the parameter `redirectToURL` will be returned. Make the player visit this URL (for example in a new popup window). Then, with the `pollToken` parameter you can periodically call the **link poll** end point. Once the user completes the sign in process from `redirectToURL`, this end point will tell you that the link request completed successfully, expired or requires further action.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://auth.construct.net/link.json
```

Authenticating The Request

This end point is for **signed in** players only.

sessionKey string Required

The **session key** of the player you're making the request against.

Request Parameters

gameID **guid** Required

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS) account**.

provider string Required

The **login provider** you wish to link (case insensitive) to this players account. Must be one of `Apple` , `BattleNet` , `Discord` , `Facebook` , `Github` , `Google` , `ItchIO` , `Microsoft` , `Patreon` , `Reddit` , `Steam` , `X` , `Yandex`

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "pollToken": "a146cc3e-2f93-4bfd-8ead-39c6cbfc7edf",
  "redirectToURL": "https://...",
  "formattingCulture": "en-us"
}
```

Response Properties

success **bool**

If the request was successfull or not.

pollToken **guid**

A polling token to get the status of the user action. For **sign in requests** use this poll token on the **sign in poll** end point. For **link requests** use this poll token on the **link poll** end point.

redirectToURL **url (string)**

The URL to the external third party login provider to complete the sign-in or link request.

formattingCulture **string**

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "You already have Discord as a sign-in method.",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/authentication/ap",
  "shouldRetry": false
}
```

Response Properties

success **bool**

If the request was successful or not.

errorMessage **string**

An error message with more detailed information on why the request failed.

helpURL **url (string)**

A link to documentation which should provide help with the error.

shouldRetry **bool**

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.