

GET A PLAYERS

View online: <https://www.construct.net/en/game-services/manuals/game-services/authentication/api-end-points/players/get-players>

Overview

This end point allows you to retrieve **expanded player objects** for your game. As the only way to query this end point is with a secret key, this should only be called by back end services.

You can specify a list of player ID's to specify explicitly, otherwise all the players in your game will be returned.

Request URL

All parameters in the request must be sent as a **POST** HTTP request. Make all requests to the following URL:

```
https://auth.construct.net/getplayers.json
```

Authenticating The Request

This end point is for **secret key** authenticated requests only. Signed in players cannot call this end point.

secret string Required

Your games **secret API key**.

Request Parameters

gameID **guid** Required

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS) account**.

order string

How you wish the players returned in this query to be ordered. Can be one of **None** , **AZ** , **ZA** , **Newest** or **oldest** . The default value if not specified is **Newest** .

playerIDs string

A comma separated list of player ID's you explicitly wish to fetch. This list cannot contain more than **300** player ID's.

perPage int32

How many players you wish to return on each page of results. Cannot be less than **1** or more than **200**. Default value is **50**.

page int32

The page of results you are requesting. The first page is always **1**. If this value is not specified the first page will be returned.

culture string Optional

Optionally specify a **supported culture code** for rendering various properties. If not specified, the culture code from your games default language will be used.

Success Response

Successful responses always return a **HTTP 200** status code.

```
{
  "success": true,
  "pagination": { ... },
  "players": [
    { ... },
    { ... }
  ],
  "formattingCulture": "en-us"
}
```

Response Properties

success bool

If the request was successful or not.

pagination **Pagination**

If there are more players returned than can be shown in one page of results, the pagination object can help you browse through the other pages of results.

players Array<**ExpandedPlayer**>

The players returned on this page of results for the query.

formattingCulture string

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/authentication/ap",
  "shouldRetry": false
}
```

Response Properties

success **bool**

If the request was successful or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry **bool**

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.