

REGISTER A PLAYER

View online: <https://www.construct.net/en/game-services/manuals/game-services/authentication/api-end-points/players/register-player>

Overview

Creates a new player in your game. This endpoint should be used for creating players without any sign in details, or creating players with a username/password set. The [sign in](#) end point can be used to register players with a third party login provider as a sign in method.

Important: By default, this end point is disabled as it opens you up to spam/fake registrations. To enable this end point, visit your games security settings.

If you want to specify a username/password for this new player, pass in the `username` and `password` parameters. If you do not specify these parameters, when the session expires the players account will become unrecoverable as there will be no way to sign in. Therefore it's strongly advised to force a username/password, or to encourage the player to either [link a login provider](#) or [set a username/password](#) before the session expires.

When a new player is registered, a new session is also created for this player and returned in the response.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://auth.construct.net/registerplayer.json
```

Authenticating The Request

No authentication is required for calling this end point, however you can optionally pass a [secret key](#) to this request. You may need to do this if you've set your game to require a secret key for `GET` or `POST` requests for this service.

secret string Optional

Your games [secret API key](#).

Request Parameters

gameID [guid](#) Required

The ID of the game you are making this request against. You can find the ID of your game in your [Construct Game Services \(CGS\) account](#).

playerName string Required

The new player name you wish to set. Name must be at least **1** character long and cannot exceed **50** characters in length. The name will also be rejected if it looks like it is an email address. Player names are the publically facing names, whereas the username is used for sign in purposes only.

username string

The username you wish to set for this new player. Usernames must be at least **3** characters long, and no more than **32** characters long. Email addresses as usernames are not permitted.

password string

The password you wish to set for this new player. Passwords must be at least **8** characters long, and no more than **32** characters long. Passwords must also contain at least one numeric, one uppercase, one lowercase, and one non-alphanumeric character.

A maximum password length is enforced because we hash passwords with **BCrypt** and CPU usages increases with password length during hashing.

expiryMins uint32

How long until the session expires. You can extend the session expiry using the [refresh session](#) end point. The default value is **1440** minutes.

Success Response

Successful responses always return a **HTTP 200** status code.

```
{
  "success": true,
  "player": { ... },
  "session": { ... },
  "formattingCulture": "en-us"
}
```

Response Properties

success bool

If the request was successful or not.

player **Player**

The newly registered player as a player object.

session **Session**

The session created for this player upon registration.

formatting**Culture string**

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return **HTTP 4xx** status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/authentication/ap",
  "shouldRetry": false
}
```

Response Properties

success **bool**

If the request was successful or not.

errorMessage **string**

An error message with more detailed information on why the request failed.

helpURL **url (string)**

A link to documentation which should provide help with the error.

shouldRetry **bool**

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.