

SIGN IN

View online: <https://www.construct.net/en/game-services/manuals/game-services/authentication/api-end-points/players/sign-in>

Overview

Sign in a player to your game with a specified **login provider**. If a sign in is successful but the third party login provider account they signed in with is not currently associated with any player in your game, a new player will be created with this sign in method attached for future sign ins.

If signing in with `UsernamePassword`, a response will immediately be returned indicating if the sign in was succesful or not and a new **session object** will be returned if the sign in was succesful.

If signing in with another login provider, a `redirectToURL` will be returned. Make the player visit this URL (for example in a new popup window). Then, with the `pollToken` parameter you can periodically call the **sign in poll** end point. Once the user completes the sign in process from `redirectToURL`, this end point will tell you that if the sign in request completed succesfully and return their newly created **session object**.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://auth.construct.net/signin.json
```

Authenticating The Request

No authentication is required for this request type.

Request Parameters

gameID **guid** Required

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS) account**.

provider string Required

The **login provider** you wish to sign in with (case insensitive). Must be one of

`UsernamePassword`, `Apple`, `BattleNet`, `Discord`, `Facebook`, `Github`, `Google`, `ItchIO`, `Microsoft`, `Patreon`, `Reddit`, `Steam`, `X`, `Yandex`

username string Sometimes required

If signing in with `UsernamePassword`, the username the player is signing in with. If specified, you must also specify `password`.

password string Sometimes required

If signing in with `UsernamePassword`, the password the player is signing in with. If specified, you must also specify `username`.

expiryMins uint32

If sign in succeeds, how long until the newly created session expires. You can extend the session expiry using the [refresh session](#) end point. The default value is `1440` minutes.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "pollToken": "b300defd-aba5-455a-a5f2-c974925e02af",
  "redirectToURL": "https://...",
  "formattingCulture": "en-us"
}
```

Response Properties

success bool

If the request was successful or not.

pollToken guid

A polling token to get the status of the user action. For [sign in requests](#) use this poll token on the [sign in poll](#) end point. For [link requests](#) use this poll token on the [link poll](#) end point.

redirectToURL url (string)

The URL to the external third party login provider to complete the sign-in or link request.

formattingCulture string

If some return values are [culture specific](#), this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "The username/password you provided are invalid.",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/authentication/ap
  "shouldRetry": false
}
```

Response Properties

success `bool`

If the request was successful or not.

errorMessage `string`

An error message with more detailed information on why the request failed.

helpURL `url (string)`

A link to documentation which should provide help with the error.

shouldRetry `bool`

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.