

SESSION OBJECT

View online: <https://www.construct.net/en/game-services/manuals/game-services/authentication/api-objects/session-object>

Example Session

```
{
  "playerID": "19a8d7af-b37c-4cfc-85e0-3954a073167a",
  "playerName": "Guffing Viking",
  "avatars": [
    { ... },
    { ... }
  ],
  "expiry": "2026-01-31T05:31:10.6065935Z",
  "gameID": "b4277837-37b0-4bc3-a0ba-9319b2650340",
  "key": "80SB!,1VGBA+AE87WE;6_ZY{=|Z4Y!^ET^7..."
}
```

Object Properties

playerID **guid**

The player ID this session belongs to.

playerName **string**

The publicly facing player name for this player.

avatars **Array<Picture>**

If player has an avatar, a list of **picture objects**. Each picture object is the same avatar, but provided in different sizes. Sizes available are based on widths, and the widths **16, 32, 64, 96, 128, 256** will be shown here along with the original avatar size if it doesn't match a width in this list. Some sizes may not show if the width is less than the original avatar width.

expiry **datetime**

The expiry date time of this session. Can be extended by calling **refresh session API end point**.

gameID **guid**

The game ID this player belongs to.

key string

The session key for this player. This should be kept private as it allows access to a players account. Session keys are randomly generated strings `128` characters long.