

LIST CHANNELS

View online: <https://www.construct.net/en/game-services/manuals/game-services/broadcasts/api-end-points/channels/list-channels>

Overview

This end point allows you to list all channels in your game. Results are not paginated, all the channels are returned in the single request.

If a player is signed in, you should pass their session key in with the request as each channel object will return if there are unread messages for that player in it.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://broadcasts.construct.net/getchannels.json
```

Authenticating The Request

No authentication is required for calling this end point, however if the request is being made by a signed in player it is recommended to pass in a `sessionKey` parameter as the request response will return additional information useful to the player.

sessionKey string Optional

The **session key** of the player who is currently signed in and making this request.

Request Parameters

gameID **guid** Required

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS) account**.

requestedLanguage **Language** Optional

Optionally specify a **language** for returning translatable properties into this language. If not specified, your games default language will be used.

culture string Optional

Optionally specify a **supported culture code** for rendering various properties. If not specified, the `requestedLanguage` default culture code will be used.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "channels": [
    { ... },
    { ... }
  ],
  "formattingCulture": "en-us"
}
```

Response Properties

success **bool**

If the request was successful or not.

channels **Array<BroadcastChannel>**

The channels returned from the request.

formattingCulture **string**

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/broadcasts/api-en",
  "shouldRetry": false
}
```

Response Properties

success **bool**

If the request was successful or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.