

GET A MESSAGE

View online: <https://www.construct.net/en/game-services/manuals/game-services/broadcasts/api-end-points/messages/get-message>

Overview

This end point allows you to retrieve a single **message**.

If a player is signed in, you should pass their session key in with the request as once the message is retrieved it will be **marked as read** for that player.

Request URL

All parameters in the request must be sent as a **POST** HTTP request. Make all requests to the following URL:

```
https://broadcasts.construct.net/getmessage.json
```

Authenticating The Request

No authentication is required for this request, but depending on what your request is requesting session key or secret key authentication may be required.

Session Key Authentication

sessionKey string Sometimes required

The **session key** of the player you're making the request against.

Secret Key Authentication

secret string Sometimes required

Your games **secret API key**.

playerID guid Sometimes required

The player ID you wish to make this request against.

Request Parameters

gameID guid Required

The ID of the game you are making this request against. You can find the ID of your game in your [Construct Game Services \(CGS\) account](#).

messageID **guid** Required

The ID of the message you want to retrieve.

requestedLanguage **Language** Optional

Optionally specify a **language** for returning translatable properties into this language. If not specified, your games default language will be used.

culture string Optional

Optionally specify a **supported culture code** for rendering various properties. If not specified, the `requestedLanguage` default culture code will be used.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "message": { ... },
  "formattingCulture": "en-us"
}
```

Response Properties

success **bool**

If the request was successful or not.

message **BroadcastMessage**

The message object returned from the request.

formattingCulture **string**

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/broadcasts/api-en-
  "shouldRetry": false
}
```

Response Properties

success **bool**

If the request was successful or not.

errorMessage **string**

An error message with more detailed information on why the request failed.

helpURL **url (string)**

A link to documentation which should provide help with the error.

shouldRetry **bool**

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.