

EDIT A BUCKET

View online: <https://www.construct.net/en/game-services/manuals/game-services/cloud-save/api-end-points/buckets/edit-bucket>

Overview

This end point allows you to update properties on an existing **bucket**.

Request URL

All parameters in the request must be sent as a **POST** HTTP request. Make all requests to the following URL:

```
https://cloudsave.construct.net/editbucket.json
```

Authenticating The Request

This end point is for **secret key** authenticated requests only. Signed in players cannot call this end point.

secret string Required

Your games **secret API key**.

Request Parameters

gameID **guid** Required

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS) account**.

bucketID **guid** Required

The ID of the bucket you wish to edit.

bucketName string

The new name of the game bucket. Omit this parameter to keep the existing name. Cannot exceed **50** characters in length. You must specify at least one of this, **accessMode**, **allowRatings**, **maxBlobSize**, **maxBlobs** Or **maxBlobsPerPlayer**.

accessMode string

The new access mode of this bucket (case insensitive). Omit this parameter to keep the existing access mode. Must be one of `Private` , `PublicRead` or `PublicReadWrite` . You must specify at least one of this, `bucketName` , `allowRatings` , `maxBlobSize` , `maxBlobs` or `maxBlobsPerPlayer` .

allowRatings **bool**

If **cloud save blobs** in this bucket can be **rated** by players. Omit this parameter to keep the existing setting. You must specify at least one of this, `bucketName` , `accessMode` , `maxBlobSize` , `maxBlobs` or `maxBlobsPerPlayer` .

maxBlobSize **int32**

The maximum size in bytes of **cloud save blobs** in this bucket. Omit this parameter to keep the existing setting. If a picture is uploaded with a blob, the size of the picture is counted towards this limit as well as the actual cloud save blob size. You must specify at least one of this, `bucketName` , `accessMode` , `allowRatings` , `maxBlobs` or `maxBlobsPerPlayer` .

maxBlobs **int32**

The maximum number of **cloud save blobs** allowed in this bucket. Omit this parameter to keep the existing name. You must specify at least one of this, `bucketName` , `accessMode` , `allowRatings` , `maxBlobSize` or `maxBlobsPerPlayer` .

maxBlobsPerPlayer **int16**

Optionally specify the maximum number of blobs an individual player can save to this bucket. You must specify at least one of this, `bucketName` , `accessMode` , `allowRatings` , `maxBlobSize` or `maxBlobs` .

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "formattingCulture": "en-us"
}
```

Response Properties

success **bool**

If the request was successfull or not.

formattingCulture **string**

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/cloud-save/api-en
  "shouldRetry": false
}
```

Response Properties

success **bool**

If the request was successful or not.

errorMessage **string**

An error message with more detailed information on why the request failed.

helpURL **url (string)**

A link to documentation which should provide help with the error.

shouldRetry **bool**

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.