

GET BUCKETS

View online: <https://www.construct.net/en/game-services/manuals/game-services/cloud-save/api-end-points/buckets/get-buckets>

Overview

This end point allows you to retrieve all existing **buckets** for your game.

Request URL

All parameters in the request must be sent as a **POST** HTTP request. Make all requests to the following URL:

```
https://cloudsave.construct.net/getbuckets.json
```

Authenticating The Request

No authentication is required for this request type.

Request Parameters

gameID **guid** Required

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS) account**.

orderBy **string**

How you wish the players returned in this query to be ordered. Can be one of **AZ** , **ZA** , **MostBlobs** , **LeastBlobs** , **MostData** or **LeastData** . The default value if not specified is **AZ** .

perPage **int32**

How many buckets you wish to return on each page of results. Cannot be less than **1** or more than **100** . Default value is **20** .

page **int32**

The page of results you are requesting. The first page is always **1** . If this value is not specified the first page will be returned.

culture **string** Optional

Optionally specify a **supported culture code** for rendering various properties. If not specified, the culture code from your games default language will be used.

Success Response

Successful responses always return a **HTTP 200** status code.

```
{
  "success": true,
  "pagination": { ... },
  "buckets": [
    { ... },
    { ... }
  ],
  "formattingCulture": "en-us"
}
```

Response Properties

success **bool**

If the request was successful or not.

pagination **Pagination**

If there are more buckets than can be displayed on one page of results, this pagination object can be used to help browse through other pages of results.

buckets **Array<Bucket>**

The buckets returned from the request.

formattingCulture **string**

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return **HTTP 4xx** status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/cloud-save/api-en-
```

```
"shouldRetry": false  
}
```

Response Properties

success **bool**

If the request was successful or not.

errorMessage **string**

An error message with more detailed information on why the request failed.

helpURL **url (string)**

A link to documentation which should provide help with the error.

shouldRetry **bool**

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.