

DELETE A CLOUD SAVE

View online: <https://www.construct.net/en/game-services/manuals/game-services/cloud-save/api-end-points/cloud-saves/delete-cloud-save>

Overview

Use this end point to delete a cloud save. Deletions are instant and permanent.

If authenticating this request as a player, the authorised player can always delete blobs they've uploaded in their own player storage or a [game bucket](#). Players cannot delete other players blobs. If authenticating with your game's secret key, you can delete any blob.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://cloudsave.construct.net/delete.json
```

Authenticating The Request

This end point can be called by [signed in](#) players, or with [secret key](#) authentication.

Session Key Authentication

sessionKey string Required

The [session key](#) of the player you're making the request against.

Secret Key Authentication

secret string Required

Your games [secret API key](#).

Request Parameters

gameID [guid](#) Required

The ID of the game you are making this request against. You can find the ID of your game in your [Construct Game Services \(CGS\) account](#).

blobID [guid](#) Required

The ID of the cloud save blob you wish to delete.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "formattingCulture": "en-us"
}
```

Response Properties

success `bool`

If the request was successful or not.

formattingCulture `string`

If some return values are `culture specific`, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/cloud-save/api-en",
  "shouldRetry": false
}
```

Response Properties

success `bool`

If the request was successful or not.

errorMessage `string`

An error message with more detailed information on why the request failed.

helpURL `url (string)`

A link to documentation which should provide help with the error.

shouldRetry **bool**

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.