

GET A CLOUD SAVE

View online: <https://www.construct.net/en/game-services/manuals/game-services/cloud-save/api-end-points/cloud-saves/get-cloud-save>

Overview

Use this end point to return a single cloud save object.

When retrieving a blob by using the `key` parameter, the following requirements must be met:

- If the blob exists in a bucket, the `bucketID` parameter must be specified.
- If the blob exists in a players account, the request must be authenticated with a session key, or if using a secret key the player ID must also be passed.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://cloudsave.construct.net/getcloudsave.json
```

Authenticating The Request

The type of authentication that is required depends on who owns the blob, and where the blob is stored.

- For cloud save blobs in `PublicRead` or `PublicReadWrite` buckets, no authentication is required.
- For cloud save blobs in `Private` buckets, authentication by secret API key is required.
- For cloud save blobs in a players account, authentication by secret API key or the players session key is required.

Session Key Authentication

sessionKey string Sometimes required

The `session key` of the player you're making the request against.

Secret Key Authentication

secret string Sometimes required

Your games [secret API key](#).

playerID [guid](#) Sometimes required

The player ID you wish to make this request against.

Request Parameters

gameID [guid](#) Required

The ID of the game you are making this request against. You can find the ID of your game in your [Construct Game Services \(CGS\) account](#).

blobID [guid](#) Sometimes required

The ID of the cloud save blob you wish to retrieve. You must specify this or `key`.

key string Sometimes required

The key of the cloud save blob you wish to retrieve. You must specify this or `blobID`.

bucketID [guid](#) Sometimes required

If fetching a cloud save blob by `key` that exists in a bucket, you must specify the bucket ID.

requestedLanguage [Language](#) Optional

Optionally specify a [language](#) for returning translatable properties into this language. If not specified, your games default language will be used.

culture string Optional

Optionally specify a [supported culture code](#) for rendering various properties. If not specified, the `requestedLanguage` default culture code will be used.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "blob": { ... },
  "formattingCulture": "en-us"
}
```

Response Properties

success **bool**

If the request was successful or not.

blob **Blob**

The blob object returned from the query.

formatting**Culture** **string**

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return **HTTP 4xx** status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/cloud-save/api-en
  "shouldRetry": false
}
```

Response Properties

success **bool**

If the request was successful or not.

errorMessage **string**

An error message with more detailed information on why the request failed.

helpURL **url (string)**

A link to documentation which should provide help with the error.

shouldRetry **bool**

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.