

GET CLOUD SAVES

View online: <https://www.construct.net/en/game-services/manuals/game-services/cloud-save/api-end-points/cloud-saves/get-cloud-saves>

Overview

Use this end point to return paginated cloud saves uploaded by a specific player.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://cloudsave.construct.net/getcloudsaves.json
```

Authenticating The Request

This end point can be called by **signed in** players, or with **secret key** authentication.

Session Key Authentication

sessionKey string Required

The **session key** of the player you're making the request against.

Secret Key Authentication

secret string Required

Your games **secret API key**.

playerID **guid** Required

The player ID you wish to make this request against.

Request Parameters

gameID **guid** Required

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS) account**.

bucketSaves **bool**

If `true` will return cloud saves player has uploaded in game buckets. If `false` will return this players private cloud saves only.

name string

Filter cloud saves by their name. Matches cloud save blobs with this whole word in the name property. Partial matches are not supported (EG: `est` will not match `my test blob` but `test` will match the blob).

key string

Filter cloud saves by their key. For example, passing `my.blob` will match `my.blob.test` and `testing.my.blob`.

orderBy string

The order you want cloud save blobs returned. Must be one of `NameAZ`, `NameZA`, `KeyAZ`, `KeyZA`, `Newest` or `Oldest`. If not specified default value is `Newest`.

perPage int32

How many cloud save blobs you wish to return on each page of results. Cannot be less than `1` or more than `100`. Default value is `10`.

page int32

The page of results you are requesting. The first page is always `1`. If this value is not specified the first page will be returned.

requestedLanguage Language Optional

Optionally specify a `language` for returning translatable properties into this language. If not specified, your games default language will be used.

culture string Optional

Optionally specify a `supported culture code` for rendering various properties. If not specified, the `requestedLanguage` default culture code will be used.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "pagination": { ... },
```

```

"blobs": [
  { ... },
  { ... }
],
"formattingCulture": "en-us"
}

```

Response Properties

success **bool**

If the request was successful or not.

pagination **Pagination**

Pagination object to assist with browsing through other pages of cloud save blobs.

blobs **Array<Blob>**

The cloud save blobs returned on this page of results.

formattingCulture **string**

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return **HTTP 4xx** status codes.

```

{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/cloud-save/api-en",
  "shouldRetry": false
}

```

Response Properties

success **bool**

If the request was successful or not.

errorMessage **string**

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.