

# RATE CLOUD SAVE

View online: <https://www.construct.net/en/game-services/manuals/game-services/cloud-save/api-end-points/ratings/rate-cloud-save>

---

## Overview

This end point allows players to rate **cloud save blobs**. You can **create rating dimensions** to allow players to vote on different aspects of cloud saves.

You can re-submit ratings to over-write their existing rating so long as it doesn't exceed the settings in your game that determine when ratings are locked from being updated. If only one rating dimension is being re-submitted, an error will throw if the rating is now locked. If multiple are being submitted, the ratings that are now locked will silently fail and the unlocked ones will be overwritten.

We strongly recommend you read about **rating concepts** to understand how ratings work.

## Request URL

All parameters in the request must be sent as a **POST** HTTP request. Make all requests to the following URL:

```
https://cloudsave.construct.net/rate.json
```

## Authenticating The Request

This end point is for **signed in** players only.

---

### sessionKey string Required

The **session key** of the player you're making the request against.

## Request Parameters

---

### gameID **guid** Required

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS) account**.

---

### thingID **guid** Required

The ID of the **cloud save blob** the player is rating.

---

## value string Required

For dimensionless ratings, simply provide the `byte` value of the rating in string format, for example: `4`. For rating on **rating dimensions**, provide a CSV list of dimension ID's and rating values, for example: `mydimension=6,anotherdimension=0`.

If a rating value exceeds the max allowed rating the rating value will be changed to the max allowed rating.

## Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "formattingCulture": "en-us"
}
```

## Response Properties

---

### success **bool**

If the request was successful or not.

---

### formattingCulture string

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

## Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/cloud-save/api-en",
  "shouldRetry": false
}
```

## Response Properties

---

### success **bool**

If the request was successful or not.

---

**errorMessage string**

An error message with more detailed information on why the request failed.

---

**helpURL url (string)**

A link to documentation which should provide help with the error.

---

**shouldRetry bool**

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.