

ADJUST A SCORE

View online: <https://www.construct.net/en/game-services/manuals/game-services/leaderboards/api-end-points/scores/adjust-score>

Overview

Adjusts the score value of an existing **score** in the leaderboard. You can pass a positive value to increase the value of the score, or a negative value to decrease it. A leaderboard must permit score adjustments in it's settings otherwise calls to adjust scores will fail.

Adjusting a score will not update the date of the score, but will increment it's updates counter.

Adjusting Score with Session Authentication

If you're calling this end point with a players session key to authenticate the request, if you do not pass in the **scoreID** parameter, the players best score will be adjusted.

Adjusting Score with Secret API Key Authentication

If you're calling this end point with a secret API key, then you need to pass in either a **scoreID** parameter or a **playerID** parameter which would adjust this players current best score.

Request URL

All parameters in the request must be sent as a **POST** HTTP request. Make all requests to the following URL:

```
https://leaderboards.construct.net/adjustscore.json
```

Authenticating The Request

This end point can be called by **signed in** players, or with **secret key** authentication.

Session Key Authentication

sessionKey string Required

The **session key** of the player you're making the request against.

Secret Key Authentication

secret string Required

Your games **secret API key**.

Request Parameters

gameID **guid** Required

The ID of the game you are making this request against. You can find the ID of your game in your [Construct Game Services \(CGS\) account](#).

leaderboardID **guid** Required

The ID of the leaderboard you're adjusting a score on.

scoreID **guid** Sometimes required

The ID of the score you're adjusting.

playerID **guid** Sometimes required

The ID of the player to adjust the score for. This parameter is only supported for requests using a secret key. If there are multiple scores for the passed player ID then this players best score will be adjusted.

adjustment **int64** Required

The amount you wish to adjust the existing score by. Pass a negative value to decrease the score, or a positive value to increase the score. The updated value must be no less than `-9223372036854775808` and no more than `9223372036854775807` otherwise an error will be returned.

hash string Sometimes required

If you are authenticating this request with a players session key, then a hash for the adjust score request must be provided. This makes it harder for players to submit fake scores or modify posted values in-flight.

A hash is generated as the SHA256 of a string of values in the request:

```
var key = (leaderboardID + "." + adjustment + "." + unixTimestamp).Normalize();  
return SHA256(key);
```

timestamp **int64** Required

The unix timestamp of the date this request was sent. (seconds since January 1st 1970, UTC). Adding historic scores or scores for future dates is not supported.

opt1 **int16**

The amount to adjust optional value 1 by. Omit this parameter to not change the existing value. The maximum value of an optional value is `32767` and the minimum value is `-32768`. If the adjustment results in a value out of these bounds, the score won't be adjusted and an error will be returned.

opt2 int16

The amount to adjust optional value 2 by. Omit this parameter to not change the existing value. The maximum value of an optional value is `32767` and the minimum value is `-32768`. If the adjustment results in a value out of these bounds, the score won't be adjusted and an error will be returned.

opt3 int16

The amount to adjust optional value 3 by. Omit this parameter to not change the existing value. The maximum value of an optional value is `32767` and the minimum value is `-32768`. If the adjustment results in a value out of these bounds, the score won't be adjusted and an error will be returned.

culture string Optional

Optionally specify a [supported culture code](#) for rendering various properties. If not specified, the culture code from your games default language will be used.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "personalBest": false,
  "score": { ... },
  "leaderboard": { ... },
  "formattingCulture": "en-us"
}
```

Response Properties

success bool

If the request was successful or not.

personalBest bool

Is this a personal best for the player who posted the score?

score **Score**

The score object for the new score.

leaderboard **LeaderboardStatus**

The status of the leaderboard after this score has been posted.

formatting**Culture string**

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return **HTTP 4xx** status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/leaderboards/api",
  "shouldRetry": false
}
```

Response Properties

success **bool**

If the request was successful or not.

errorMessage **string**

An error message with more detailed information on why the request failed.

helpURL **url (string)**

A link to documentation which should provide help with the error.

shouldRetry **bool**

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.