

GET SCORE NEIGHBOURS

View online: <https://www.construct.net/en/game-services/manuals/game-services/leaderboards/api-end-points/scores/get-score-neighbours>

Overview

Given a player ID or a score record ID, get the surrounding scores in the leaderboard.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://leaderboards.construct.net/getscoreneighbours.json
```

Authenticating The Request

No authentication is required for calling this end point, however you can optionally pass a **secret key** to this request. You may need to do this if you've set your game to require a secret key for `GET` or `POST` requests for this service.

secret string Optional

Your games **secret API key**.

Request Parameters

gameID **guid** Required

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS) account**.

leaderboardID **guid** Required

The ID of the leaderboard you're fetching the scores for.

playerID **guid** Sometimes required

The player ID to query. You must specify this or `scoreID`.

scoreID **guid** Sometimes required

The ID of the score to query. You must specify this or `playerID`.

range int16

How many scores to return on either side of the queried score. If no value is specified, or an invalid value is specified this defaults to `5` which will return up to 11 scores (the queried score, plus up to 5 scores on each side). The maximum value allowed is `50`.

compareRanks int16

Optionally specify this value for leaderboards that support score history tracking. This value represents how many days ago you wish to compare returned scores in this query to. For example, if 10 is specified then the relevant score history object will be returned in the score object representing what this score was 10 days ago.

requesterIP string

If using secret key authentication, you can pass an IP address here to return results as if this IP address made the request. This is useful when building your own implementation and ensuring shadow banned scores are properly hidden/shown to the end user.

culture string Optional

Optionally specify a [supported culture code](#) for rendering various properties. If not specified, the culture code from your games default language will be used.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "pagination": { ... },
  "scores": [
    { ... },
    { ... }
  ],
  "formattingCulture": "en-us"
}
```

Response Properties

success bool

If the request was successful or not.

pagination [Pagination](#)

A pagination object helpful for navigating other pages of results.

scores Array<Score>

The list of score objects returned from the request.

formatting Culture string

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/leaderboards/api",
  "shouldRetry": false
}
```

Response Properties

success bool

If the request was successful or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.