

GET IP SHADOW BANS

View online: <https://www.construct.net/en/game-services/manuals/game-services/leaderboards/api-end-points/shadow-bans/get-ip-bans>

Overview

Retrieve a list of all IP hashes that have been shadow banned.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://leaderboards.construct.net/getipshadowbans.json
```

Authenticating The Request

This end point is for `secret key` authenticated requests only. Signed in players cannot call this end point.

secret string Required

Your games `secret API key`.

Request Parameters

gameID `guid` Required

The ID of the game you are making this request against. You can find the ID of your game in your [Construct Game Services \(CGS\) account](#).

leaderboardID `guid` Required

The ID of the leaderboard you're fetching the shadow bans for.

perPage int32

How many bans you wish to return on each page of results. Cannot be less than `1` or more than `500`. Default value is `20`.

page int32

The page of results you are requesting. The first page is always **1**. If this value is not specified the first page will be returned.

culture string Optional

Optionally specify a **supported culture code** for rendering various properties. If not specified, the culture code from your games default language will be used.

Success Response

Successful responses always return a **HTTP 200** status code.

```
{
  "success": true,
  "bans": [
    { ... },
    { ... }
  ],
  "pagination": { ... },
  "formattingCulture": "en-us"
}
```

Response Properties

success **bool**

If the request was successful or not.

bans Array<**IPShadowBan**>

The list of IP shadow bans returned in the request.

pagination **Pagination**

A pagination object helpful for navigating other pages of results.

formattingCulture string

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return **HTTP 4xx** status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/leaderboards/api",
  "shouldRetry": false
}
```

Response Properties

success **bool**

If the request was successful or not.

errorMessage **string**

An error message with more detailed information on why the request failed.

helpURL **url (string)**

A link to documentation which should provide help with the error.

shouldRetry **bool**

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.