

REMOVE A SHADOW BAN FROM PLAYER OR IP

View online: <https://www.construct.net/en/game-services/manuals/game-services/leaderboards/api-end-points/shadow-bans/remove-shadow-ban>

Overview

Remove an existing shadow ban from a leaderboard. Shadow bans can be on player ID's or IP addresses.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://leaderboards.construct.net/unshadowban.json
```

Authenticating The Request

This end point is for `secret key` authenticated requests only. Signed in players cannot call this end point.

secret string Required

Your games `secret API key`.

Request Parameters

gameID `guid` Required

The ID of the game you are making this request against. You can find the ID of your game in your `Construct Game Services (CGS) account`.

leaderboardID `guid` Required

The ID of the leaderboard you're removing the shadow ban from.

playerID `guid` Sometimes required

The player ID to remove the shadow ban from. You must specify this, `scoreID` , `ipAddress` or `ipHash` .

scoreID **guid** Sometimes required

The score ID to remove the shadow ban from. Providing this will remove the shadow ban for the player + IP address associated with this score record. You must specify this, `playerID`, `ipAddress` or `ipHash`.

ipAddress string Sometimes required

The IP address to remove the shadow ban from.. You must specify this, `playerID`, `scoreID` or `ipHash`.

ipHash int32 Sometimes required

The IP hash to remove the shadow ban from.. You must specify this, `playerID`, `scoreID` or `ipAddress`.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "formattingCulture": "en-us"
}
```

Response Properties

success **bool**

If the request was successful or not.

formattingCulture string

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/leaderboards/api.",
  "shouldRetry": false
}
```

Response Properties

success **bool**

If the request was successful or not.

errorMessage **string**

An error message with more detailed information on why the request failed.

helpURL **url (string)**

A link to documentation which should provide help with the error.

shouldRetry **bool**

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.