

DELETE A TEAM

View online: <https://www.construct.net/en/game-services/manuals/game-services/leaderboards/api-end-points/teams/delete-team>

Overview

Delete a **team** from a leaderboard.

Request URL

All parameters in the request must be sent as a **POST** HTTP request. Make all requests to the following URL:

```
https://leaderboards.construct.net/deleteteam.json
```

Authenticating The Request

This end point is for **secret key** authenticated requests only. Signed in players cannot call this end point.

secret string Required

Your games **secret API key**.

Request Parameters

gameID **guid** Required

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS) account**.

leaderboardID **guid** Required

The ID of the leaderboard you're deleting scores on.

teamID **guid** Required

The ID of the team you're deleting.

Success Response

Successful responses always return a **HTTP 200** status code.

```
{
  "success": true,
  "formattingCulture": "en-us"
}
```

Response Properties

success bool

If the request was successful or not.

formattingCulture string

If some return values are culture specific, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return HTTP 4xx status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/leaderboards/api",
  "shouldRetry": false
}
```

Response Properties

success bool

If the request was successful or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.