

GET TEAMS

View online: <https://www.construct.net/en/game-services/manuals/game-services/leaderboards/api-end-points/teams/get-teams>

Overview

Retrieve all **teams**, ordered by the highest rank.

Request URL

All parameters in the request must be sent as a **POST** HTTP request. Make all requests to the following URL:

```
https://leaderboards.construct.net/getteams.json
```

Authenticating The Request

No authentication is required for calling this end point, however you can optionally pass a **secret key** to this request. You may need to do this if you've set your game to require a secret key for **GET** or **POST** requests for this service.

secret string Optional

Your games **secret API key**.

Request Parameters

gameID **guid** Required

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS) account**.

leaderboardID **guid** Required

The ID of the leaderboard you're fetching teams from.

order string

How you wish the teams returned in this query to be ordered. Can be one of **BestRanked**, **WorstRanked**, **NameAZ**, **NameZA**, **MostPlayers**, **LeastPlayers**, **Newest** or **Oldest**. The default value if not specified is **Newest**.

How many teams you wish to return on each page of results. Cannot be less than **1** or more than **100**. Default value is **20**.

page int32

The page of results you are requesting. The first page is always **1**. If this value is not specified the first page will be returned.

culture string Optional

Optionally specify a **supported culture code** for rendering various properties. If not specified, the culture code from your games default language will be used.

Success Response

Successful responses always return a **HTTP 200** status code.

```
{
  "success": true,
  "pagination": { ... },
  "teams": [
    { ... },
    { ... }
  ],
  "formattingCulture": "en-us"
}
```

Response Properties

success bool

If the request was successful or not.

pagination **Pagination**

A pagination object helpful for navigating other pages of results.

teams Array<**ExpandedTeam**>

The list of team objects returned from the request.

formattingCulture string

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/leaderboards/api",
  "shouldRetry": false
}
```

Response Properties

success `bool`

If the request was successful or not.

errorMessage `string`

An error message with more detailed information on why the request failed.

helpURL `url (string)`

A link to documentation which should provide help with the error.

shouldRetry `bool`

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.