

GET PLAYERS ON A TEAM

View online: <https://www.construct.net/en/game-services/manuals/game-services/leaderboards/api-end-points/teams/team-players>

Overview

Returns all players currently registered on a **team**.

Request URL

All parameters in the request must be sent as a **POST** HTTP request. Make all requests to the following URL:

```
https://leaderboards.construct.net/getteampayers.json
```

Authenticating The Request

No authentication is required for calling this end point, however you can optionally pass a **secret key** to this request. You may need to do this if you've set your game to require a secret key for **GET** or **POST** requests for this service.

secret string Optional

Your games **secret API key**.

Request Parameters

gameID **guid** Required

The ID of the game you are making this request against. You can find the ID of your game in your **Construct Game Services (CGS) account**.

culture string Optional

Optionally specify a **supported culture code** for rendering various properties. If not specified, the culture code from your games default language will be used.

Success Response

Successful responses always return a **HTTP 200** status code.

```
{  
  "success": true,
```

```

"pagination": { ... },
"players": [
  { ... },
  { ... }
],
"team": { ... },
"formattingCulture": "en-us"
}

```

Response Properties

success **bool**

If the request was successful or not.

pagination **Pagination**

A pagination object helpful for navigating other pages of results.

players **Array<TeamPlayer>**

The list of players returned in the request.

team **ExpandedTeam**

The team object these players belong to.

formattingCulture **string**

If some return values are **culture specific**, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return **HTTP 4xx** status codes.

```

{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/leaderboards/api",
  "shouldRetry": false
}

```

Response Properties

success **bool**

If the request was successful or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.