# GET AN ACHIEVEMENT

**View online:** https://www.construct.net/en/game-services/manuals/game-services/achievements/api-end-points/achievements/get-achievement

## Overview

This end point allows you to get an existing achievement. If the achievement being fetched is `secret=true` the response will only succeed if the request is authenticated with a secret API key.

## Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://achievements.construct.net/getachievement.json
```

## Authenticating The Request

No authentication is required for calling this end point.

**secret string Optional**

Your games secret API key.

## Request Parameters

**gameID guid Required**

The ID of the game you are making this request against. You can find the ID of your game in your Construct Game Services (CGS) account.

**achievementID string Required**

The unique ID of the achievement you want to get.

**culture string Optional**

Optionally specify a supported culture code for rendering various properties. If not specified, the culture code from your games default language will be used.

## Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "achievement": { ... },
  "formattingCulture": "en-us"
}
```

### Response Properties

**success bool**

If the request was successfull or not.

**achievement Achievement**

An Achievement object.

**formattingCulture string**

If some return values are culture specific, this property indicates what culture the values have been rendered as.

## Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Achievement doesn't exist.",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/achievements/api-
  "shouldRetry": false
}
```

### Response Properties

**success bool**

If the request was successfull or not.

**errorMessage string**

An error message with more detailed information on why the request failed.

**helpURL url (string)**

A link to documentation which should provide help with the error.

---

**shouldRetry** bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.