# DELETE PLAYER AVATAR

**View online:** https://www.construct.net/en/game-services/manuals/game-services/authentication/api-end-points/avatars/delete-avatar

## Overview

Use this end point to delete a players avatar if they have one set. If this is called and the player doesn't have an avatar, it will still return a success response. Failure responses should only be returned if authentication fails, or there is a network error.

## Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://auth.construct.net/deleteavatar.json
```

## Authenticating The Request

This end point can be called by signed in players, or with secret key authentication.

### Session Key Authentication

**sessionKey string Required**

The session key of the player you're making the request against.

### Secret Key Authentication

**secret string Required**

Your games secret API key.

**playerID guid Required**

The player ID you wish to make this request against.

## Request Parameters

**gameID guid Required**

The ID of the game you are making this request against. You can find the ID of your game in your Construct Game Services (CGS) account.

# Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "formattingCulture": "en-us"
}
```

## Response Properties

**success bool**

If the request was successfull or not.

**formattingCulture string**

If some return values are culture specific, this property indicates what culture the values have been rendered as.

# Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/authentication/ap
  "shouldRetry": false
}
```

## Response Properties

**success bool**

If the request was successfull or not.

**errorMessage string**

An error message with more detailed information on why the request failed.

**helpURL url (string)**

A link to documentation which should provide help with the error.

**shouldRetry bool**

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.