SET PLAYER AVATAR

View online: https://www.construct.net/en/game-services/manuals/game-services/authentication/api-end-points/avatars/set-avatar

Overview

Sets a players avatar, overwriting the existing one if the player already has an avatar set. Supported avatar file types are `Gif`, `Jpeg`, `Png`, `WebP`, `SVG`. The minimum avatar size is `32x32` pixels and the maximum avatar size is `2048x2048` pixels. The maximum file size of uploaded avatars depends on your CGS plan - please refer to your CGS account to find this value.

If a player is restricted from setting an avatar with the `Upload Avatar` restriction,, an error will be returned unless a game API key is used to authenticate the request.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://auth.construct.net/setavatar.json
```

Authenticating The Request

This end point can be called by signed in players, or with secret key authentication.

Session Key Authentication

sessionKey string Required

The session key of the player you're making the request against.

Secret Key Authentication

secret string Required

Your games secret API key.

playerID guid Required

The player ID you wish to make this request against.

Request Parameters

gameID guid Required

The ID of the game you are making this request against. You can find the ID of your game in your Construct Game Services (CGS) account.

avatar string Sometimes required

The base64 encoded avatar picture being set for this player. You must specify this, `avatarURL` or `avatarData`.

avatarURL url (string) Sometimes required

The absolute URL of the avatar being set for this player. You must specify this, `avatar` or `avatarData`.

File Data

This request additionally supports the posting of files. These files should be sent as `multipart/form-data,` with the corresponding keys.

avatarData multipart/form-data Sometimes required

The data of the avatar image being set for this player. You must specify this, `avatar` or `avatarURL`.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "avatars": [
    { ... },
    { ... }
  ],
  "formattingCulture": "en-us"
}
```

Response Properties

success bool

If the request was successfull or not.

avatars Array<Picture>

A list of picture objects representing the players new avatar. Each picture object is the same avatar, but provided in different sizes. Sizes available are based on widths, and the widths `16, 32, 64, 96, 128, 256` will be shown here along with the original avatar size if it doesn't match a width in this list. Some sizes may not show if the width is less than the original avatar width.

---

formattingCulture string

If some return values are culture specific, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.


```
{
  "success": false,
  "errorMessage": "The image provided is not valid Base64 data.",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/authentication/ap
  "shouldRetry": false
}
```


Response Properties

---

success bool

If the request was successfull or not.

---

errorMessage string

An error message with more detailed information on why the request failed.

---

helpURL url (string)

A link to documentation which should provide help with the error.

---

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.