CHANGE PLAYER NAME

View online: https://www.construct.net/en/game-services/manuals/game-services/authentication/api-end-points/players/change-player-name

Overview

Use this end point to change a players player name if they have one set. The player name is the publiclly facing name you can display to other players.

If the player is restricted from changing their player name with the `Change Player Name` restriction, the name can only be changed if the request is authenticated with a secret key.

In your CGS account you are able to maintain a list of banned player name words. If any of these words are found in the requested player name, the name will be rejected and an error returned.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://auth.construct.net/changeplayername.json
```

Authenticating The Request

This end point can be called by signed in players, or with secret key authentication.

Session Key Authentication

sessionKey string Required

The session key of the player you're making the request against.

Secret Key Authentication

secret string Required

Your games secret API key.

playerID guid Required

The player ID you wish to make this request against.

Request Parameters

gameID guid Required

The ID of the game you are making this request against. You can find the ID of your game in your Construct Game Services (CGS) account.

playerName string Required

The new player name you wish to set. Name must be at least `1` character long and cannot exceed `50` characters in length. The name will also be rejected if it looks like it is an email address.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "formattingCulture": "en-us"
}
```

Response Properties

success bool

If the request was successfull or not.

formattingCulture string

If some return values are culture specific, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/authentication/ap
  "shouldRetry": false
}
```

Response Properties

success bool

If the request was successfull or not.

---

errorMessage string

An error message with more detailed information on why the request failed.

---

helpURL url (string)

A link to documentation which should provide help with the error.

---

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.