FORGOTTEN PASSWORD

View online: https://www.construct.net/en/game-services/manuals/game-services/authentication/api-end-points/players/forgotten-password

Overview

This is only supported if your plan includes email credits. If a user has a verified email address, they can use this end point to request a password reset.

When the link in the email is clicked, the user will be redirected to a web page allowing them to enter a new password. If the user does not have a username or password, it will allow them to create one. The link is valid for 15 minutes.

For security and privacy reasons, a success message will always be shown for this request unless there is an issue with the format of the email address provided (for example it's too short or it's not a valid email address).

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://auth.construct.net/forgottenpassword.json
```

Authenticating The Request

No authentication is required for this request type.

Request Parameters

gameID guid Required

The ID of the game you are making this request against. You can find the ID of your game in your Construct Game Services (CGS) account.

emailAddress string Required

The email address of the user requesting the forgotten password. This email address must be tied to a players account who has a verified email address.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "formattingCulture": "en-us"
}
```

Response Properties

success bool

If the request was successfull or not.

formattingCulture string

If some return values are culture specific, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/authentication/ap
  "shouldRetry": false
}
```

Response Properties

success bool

If the request was successfull or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.