LIST PLAYERS

View online: https://www.construct.net/en/game-services/manuals/game-services/authentication/api-end-points/players/list-players

Overview

This end point allows you to retrieve expanded player objects for your game. As the only way to query this end point is with a secret key, this should only be called by back end services.

You can specify a list of player ID's to specify explicitly, otherwise all the players in your game will be returned.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://auth.construct.net/listplayers.json
```

Authenticating The Request

This end point is for secret key authenticated requests only. Signed in players cannot call this end point.

secret string Required

Your games secret API key.

Request Parameters

gameID guid Required

The ID of the game you are making this request against. You can find the ID of your game in your Construct Game Services (CGS) account.

order string

How you wish the players returned in this query to be ordered. Can be one of `None`, `AZ`, `ZA`, `Newest`, `Oldest` or `MostRecentlyActive`. The default value if not specified is `Newest`.

playerIDs string

A comma separated list of player ID's you explicitly wish to fetch. This list cannot contain more than `300` player ID's.

---

perPage int32

How many players you wish to return on each page of results. Cannot be less than `1` or more than `200`. Default value is `50`.

---

page int32

The page of results you are requesting. The first page is always `1`. If this value is not specified the first page will be returned.

---

culture string Optional

Optionally specify a supported culture code for rendering various properties. If not specified, the culture code from your games default language will be used.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "pagination": { ... },
  "players": [
    { ... },
    { ... }
  ],
  "formattingCulture": "en-us"
}
```

Response Properties

---

success bool

If the request was successfull or not.

---

pagination Pagination

If there are more players returned than can be shown in one page of results, the pagination object can help you browse through the other pages of results.

---

players Array<ExpandedPlayer>

The players returned on this page of results for the query.

formattingCulture string

If some return values are culture specific, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/authentication/ap
  "shouldRetry": false
}
```

Response Properties

success bool

If the request was successfull or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.