SESSION OBJECT

View online: https://www.construct.net/en/game-services/manuals/game-services/authentication/api-objects/session-object

Example Session

```
{
  "playerID": "ea4f2fbb-720c-425b-aa51-582f3516e802",
  "playerName": "Guffing Viking",
  "avatars": [
    { ... },
    { ... }
  ],
  "expiry": "2026-06-01T11:42:38.2813449Z",
  "gameID": "9db9053e-7180-487d-ba1d-9239666c4fb7",
  "key": "80SB!,1VGBA+AE87WE;6_ZY{=|Z4Y!^ET^7..."
}
```

Object Properties

playerID guid

The player ID this session belongs to.

playerName string

The publicly facing player name for this player.

avatars Array<Picture>

If player has an avatar, a list of picture objects. Each picture object is the same avatar, but provided in different sizes. Sizes available are based on widths, and the widths `16, 32, 64, 96, 128, 256` will be shown here along with the original avatar size if it doesn't match a width in this list. Some sizes may not show if the width is less than the original avatar width.

expiry datetime

The expiry date time of this session. Can be extended by calling refresh session API end point.

gameID guid

The game ID this player belongs to.

key string

The session key for this player. This should be kept private as it allows access to a players account. Session keys are randomly generated strings `128` characters long.