# CREATE A BUCKET

**View online:** https://www.construct.net/en/game-services/manuals/game-services/cloud-save/api-end-points/buckets/create-bucket

## Overview

This end point allows you to create a bucket. Game buckets are containers that can hold multiple cloud save blobs.

You can set up buckets with different access modes. For example, create a `PublicRead` bucket to upload game content to which players can only read from. Or, create a `PublicReadWrite` bucket to allow players to upload shared content such as level designs.

`Private` buckets cannot be written to or read from by players - you typically don't need these but they can be used for more advanced implementations.

## Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://cloudsave.construct.net/createbucket.json
```

## Authenticating The Request

This end point is for secret key authenticated requests only. Signed in players cannot call this end point.

**secret string Required**

Your games secret API key.

## Request Parameters

**gameID guid Required**

The ID of the game you are making this request against. You can find the ID of your game in your Construct Game Services (CGS) account.

**bucketName string Required**

The name of the game bucket you're creating. Cannot exceed `50` characters in length.

**accessMode string Required**

The access mode of this bucket (case insensitive). Must be one of `Private`, `PublicRead` or `PublicReadWrite`.

**allowRatings bool Required**

If cloud save blobs in this bucket can be rated by players.

**maxBlobs int32**

Optionally specify the maximum number of cloud save blobs allowed in this bucket.

**maxBlobSize int32**

Optionally specify the maximum size in bytes of cloud save blobs in this bucket. If a picture is uploaded with a blob, the size of the picture is counted towards this limit as well as the actual cloud save blob size.

**maxBlobsPerPlayer int16**

Optionally specify the maximum number of blobs an individual player can save to this bucket.

# Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "bucket": { ... },
  "formattingCulture": "en-us"
}
```

## Response Properties

**success bool**

If the request was successfull or not.

**bucket Bucket**

The bucket returned from the request.

**formattingCulture string**

If some return values are culture specific, this property indicates what culture the values have been rendered as.

## Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/cloud-save/api-er
  "shouldRetry": false
}
```

### Response Properties

---

**success** bool

If the request was successfull or not.

---

**errorMessage** string

An error message with more detailed information on why the request failed.

---

**helpURL** url (string)

A link to documentation which should provide help with the error.

---

**shouldRetry** bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.