GET A CLOUD SAVE

View online: https://www.construct.net/en/game-services/manuals/game-services/cloud-save/api-end-points/cloud-saves/get-cloud-save

Overview

Use this end point to return a single cloud save object.

When retrieving a blob by using the `key` parameter, the following requirements must be met:

- If the blob exists in a bucket, the `bucketID` parameter must be specified.
- If the blob exists in a players account, the request must be authenticated with a session key, or if using a secret key the player ID must also be passed.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://cloudsave.construct.net/getcloudsave.json
```

Authenticating The Request

The type of authentication that is required depends on who owns the blob, and where the blob is stored.

- For cloud save blobs in `PublicRead` or `PublicReadWrite` buckets, no authentication is required.
- For cloud save blobs in `Private` buckets, authentication by secret API key is required.
- For cloud save blobs in a players account, authentication by secret API key or the players session key is required.

Session Key Authentication

sessionKey string Optional

The session key of the player you're making the request against.

Secret Key Authentication

secret string Optional

Your games secret API key.

Request Parameters

gameID guid Required

The ID of the game you are making this request against. You can find the ID of your game in your Construct Game Services (CGS) account.

blobID guid Sometimes required

The ID of the cloud save blob you wish to retrieve. You must specify this or `key`.

key string Sometimes required

The key of the cloud save blob you wish to retrieve. You must specify this or `blobID`.

bucketID guid Sometimes required

If fetching a cloud save blob by `key` that exists in a bucket, you must specify the bucket ID.

requestedLanguage Language Optional

Optionally specify a language for returning translatable properties into this language. If not specified, your games default language will be used.

culture string Optional

Optionally specify a supported culture code for rendering various properties. If not specified, the `requestedLanguage` default culture code will be used.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "blob": { ... },
  "formattingCulture": "en-us"
}
```

Response Properties

success bool

If the request was successfull or not.

blob Blob

The blob object returned from the query.

formattingCulture string

If some return values are culture specific, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/cloud-save/api-er
  "shouldRetry": false
}
```

Response Properties

success bool

If the request was successfull or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.