CREATE RATING DIMENSION

View online: https://www.construct.net/en/game-services/manuals/game-services/cloud-save/api-end-points/ratings/create-dimension

Overview

This end point allows you to create a new rating dimension for a game bucket - all cloud save blobs in that bucket can then be rated using that dimension.

We strongly recommend you read about rating concepts to understand how dimensions in ratings work.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://cloudsave.construct.net/bucketcreateratingdimension.json
```

Authenticating The Request

This end point is for secret key authenticated requests only. Signed in players cannot call this end point.

secret string Required

Your games secret API key.

Request Parameters

gameID guid Required

The ID of the game you are making this request against. You can find the ID of your game in your Construct Game Services (CGS) account.

thingID guid Required

The ID of the game bucket you're creating a rating dimension for.

dimensionID string Required

The ID of the rating dimension you're creating. Must be unique for this game bucket. Cannot exceed `50` characters in length and must only contain alpha-numeric, dots (.) and dash (-)

characters. Once set, this ID cannot be changed.

---

title string

The title of this rating dimension. Cannot exceed `128` characters in length.

---

description string

The description of this rating dimension. Cannot exceed `1024` characters in length.

---

maxRating uint8 Required

The maximum allowed rating value. `0` is always permitted, so the minimum permitted value is `1` and the maximum permitted value is `255`.

---

language string

Provide this parameter to set the language that the title and description of this dimension are written in. Permitted values are `AR`, `BG`, `CS`, `DA`, `DE`, `EL`, `EN`, `ES`, `ET`, `FI`, `FR`, `HE`, `HU`, `ID`, `IT`, `JA`, `KO`, `LT`, `LV`, `NB`, `NL`, `PL`, `PT`, `RO`, `RU`, `SK`, `SL`, `SV`, `TH`, `TR`, `UK`, `VI`, `ZH`.

---

requestedLanguage Language Optional

Optionally specify a language for returning translatable properties into this language. If not specified, your games default language will be used.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "dimension": { ... },
  "formattingCulture": "en-us"
}
```

Response Properties

---

success bool

If the request was successfull or not.

---

dimension RatingDimension

The returned dimension for the request.

formattingCulture string

If some return values are culture specific, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/cloud-save/api-er
  "shouldRetry": false
}
```

Response Properties

success bool

If the request was successfull or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.