CREATE A RANK

View online: https://www.construct.net/en/game-services/manuals/game-services/xp/api-end-points/ranks/create-rank

Overview

This end point allows you to create a new XP rank.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://xp.construct.net/createrank.json
```

Authenticating The Request

This end point is for secret key authenticated requests only. Signed in players cannot call this end point.

secret string Required

Your games secret API key.

Request Parameters

gameID guid Required

The ID of the game you are making this request against. You can find the ID of your game in your Construct Game Services (CGS) account.

xp int64 Required

The XP level required to achieve this rank.

title string Required

A title for the rank, for example 'General'.

description string

A description for the rank.

language string

Provide this parameter to set the language that the title and description are written in. Permitted values are `AR`, `BG`, `CS`, `DA`, `DE`, `EL`, `EN`, `ES`, `ET`, `FI`, `FR`, `HE`, `HU`, `ID`, `IT`, `JA`, `KO`, `LT`, `LV`, `NB`, `NL`, `PL`, `PT`, `RO`, `RU`, `SK`, `SL`, `SV`, `TH`, `TR`, `UK`, `VI`, `ZH`. If not specified, your games default language will be used.

logo string

If uploading a logo for this rank, the base64 encoded logo picture data. If specified, you can't specify `logoURL` or `logoData`.

logoURL url (string)

If setting a logo for this rank, the absolute URL of the logo. If specified, you can't specify `logo` or `logoData`.

culture string Optional

Optionally specify a supported culture code for rendering various properties. If not specified, the culture code from your games default language will be used.

File Data

This request additionally supports the posting of files. These files should be sent as `multipart/form-data,` with the corresponding keys.

logoData multipart/form-data

If setting a logo for this rank, the binary data for the logo. If specified, you can't specify `logo` or `logoURL`.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "rank": { ... },
  "formattingCulture": "en-us"
}
```

Response Properties

success bool

If the request was successfull or not.

---

rank XPRank

An XP rank object.

---

formattingCulture string

If some return values are culture specific, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/xp/api-end-points
  "shouldRetry": false
}
```

Response Properties

---

success bool

If the request was successfull or not.

---

errorMessage string

An error message with more detailed information on why the request failed.

---

helpURL url (string)

A link to documentation which should provide help with the error.

---

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.