GET ALL PLAYERS LOGIN PROVIDERS

View online: https://www.construct.net/en/game-services/manuals/game-services/authentication/api-end-points/login-providers/get-login-providers

Overview

Returns all the login providers currently connected to a player (all the login providers this player can use to sign into their player account with).

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://auth.construct.net/getconnectedloginproviders.json
```

Authenticating The Request

This end point is for signed in players only.

sessionKey string Required

The session key of the player you're making the request against.

Request Parameters

gameID guid Required

The ID of the game you are making this request against. You can find the ID of your game in your Construct Game Services (CGS) account.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "connectedProviders": [
    { ... },
    { ... }
  ],
```

```
  "formattingCulture": "en-us"
}
```

Response Properties

success bool

If the request was successfull or not.

connectedProviders Array<PlayerLoginProvider>

A list of login providers this player is able to sign in with.

formattingCulture string

If some return values are culture specific, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/authentication/ap
  "shouldRetry": false
}
```

Response Properties

success bool

If the request was successfull or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.