SET EMAIL ADDRESS

View online: https://www.construct.net/en/game-services/manuals/game-services/authentication/api-end-points/players/set-email-address

Overview

A player in your game can choose to set or update the email address of their account with this end point. Email addresses must be in a valid email format, and must be unique across all players in your game. If the email address provided is already in use by another player, you will receive an error response.

If your plan supports it, an email will be sent to this player asking them to click a link to verify their email address. Only verified emails can use the email sign in method. If your plan does not support emails, the email address will be set for the player but will remain in an unverified state.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://auth.construct.net/setemailaddress.json
```

Authenticating The Request

This end point can be called by signed in players, or with secret key authentication.

Session Key Authentication

sessionKey string Required

The session key of the player you're making the request against.

Secret Key Authentication

secret string Required

Your games secret API key.

playerID guid Required

The player ID you wish to make this request against.

Request Parameters

gameID guid Required

The ID of the game you are making this request against. You can find the ID of your game in your Construct Game Services (CGS) account.

emailAddress string Sometimes required

The email address you wish to set for this player. Send an empty value to have any email address currently set for this player to be removed.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "formattingCulture": "en-us"
}
```

Response Properties

success bool

If the request was successfull or not.

formattingCulture string

If some return values are culture specific, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/authentication/ap
  "shouldRetry": false
}
```

Response Properties

success bool

If the request was successfull or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.