SET USERNAME + PASSWORD

View online: https://www.construct.net/en/game-services/manuals/game-services/authentication/api-end-points/players/set-username-password

Overview

You can use this end point for the following purposes:

- Setting a username/password for a player to sign in with if they do not have a username/password set. If the player has no username/password, both `username` and `password` parameters must be sent in the request.
- Changing their currently set username/password if they currently have one set. If you only wish to change the username, only send the `username` parameter. If you only want to change their password, only send the `password` parameter. Or, you can send both parameters to update both at the same time.

Usernames should be considered secret, and not exposed to other players. The `playerName` should be showed publiclly. Usernames cannot be email addresses.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://auth.construct.net/setusernamepassword.json
```

Authenticating The Request

This end point can be called by signed in players, or with secret key authentication.

Session Key Authentication

sessionKey string Required

The session key of the player you're making the request against.

Secret Key Authentication

secret string Required

Your games secret API key.

playerID guid Required

The player ID you wish to make this request against.

Request Parameters

gameID guid Required

The ID of the game you are making this request against. You can find the ID of your game in your Construct Game Services (CGS) account.

username string Sometimes required

The username you wish to set for this player. Usernames must be at least `3` characters long, and no more than `32` characters long. Email addresses as usernames are not permitted.

password string Sometimes required

The password you wish to set for this player. Passwords must be at least `8` characters long, and no more than `32` characters long. Passwords must also contain at least one numeric, one uppercase, one lowercase, and one non-alphanumeric character.

A maximum password length is enforced because we hash passwords with `BCrypt` and CPU usages increases with password length during hashing.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "formattingCulture": "en-us"
}
```

Response Properties

success bool

If the request was successfull or not.

formattingCulture string

If some return values are culture specific, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/authentication/ap
  "shouldRetry": false
}
```

Response Properties

---

success bool

If the request was successfull or not.

---

errorMessage string

An error message with more detailed information on why the request failed.

---

helpURL url (string)

A link to documentation which should provide help with the error.

---

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.