CREATE A MESSAGE

View online: https://www.construct.net/en/game-services/manuals/game-services/broadcasts/api-end-points/messages/create-message

Overview

This end point allows you to create a new message in a channel.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://broadcasts.construct.net/createmessage.json
```

Authenticating The Request

This end point is for secret key authenticated requests only. Signed in players cannot call this end point.

secret string Required

Your games secret API key.

Request Parameters

gameID guid Required

The ID of the game you are making this request against. You can find the ID of your game in your Construct Game Services (CGS) account.

channelID guid Required

The ID of the channel you are publishing this message to.

title string

A title for this message. If specified, the maximum length of the title can be found in your plan settings.

text string Required

The text of this message. Can be in any text format, for example HTML, BBCode or just plain text.

---

language string

Provide this parameter to update the language that the name and description of this channel are written in. Permitted values are `AR` , `BG` , `CS` , `DA` , `DE` , `EL` , `EN` , `ES` , `ET` , `FI` , `FR` , `HE` , `HU` , `ID` , `IT` , `JA` , `KO` , `LT` , `LV` , `NB` , `NL` , `PL` , `PT` , `RO` , `RU` , `SK` , `SL` , `SV` , `TH` , `TR` , `UK` , `VI` , `ZH` . If not specified, your channels language will be used.

---

requestedLanguage Language Optional

Optionally specify a language for returning translatable properties into this language. If not specified, your games default language will be used.

---

culture string Optional

Optionally specify a supported culture code for rendering various properties. If not specified, the `requestedLanguage` default culture code will be used.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "message": { ... },
  "formattingCulture": "en-us"
}
```

Response Properties

---

success bool

If the request was successfull or not.

---

message BroadcastMessage

The message object returned from the request.

---

formattingCulture string

If some return values are culture specific, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/broadcasts/api-er
  "shouldRetry": false
}
```

Response Properties

---

success bool

If the request was successfull or not.

---

errorMessage string

An error message with more detailed information on why the request failed.

---

helpURL url (string)

A link to documentation which should provide help with the error.

---

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.