EDIT RATING DIMENSION

View online: https://www.construct.net/en/game-services/manuals/game-services/broadcasts/api-end-points/ratings/edit-dimension

Overview

This end point allows you to update properties on an existing rating dimension setup on a channel.

We strongly recommend you read about rating concepts to understand how dimensions in ratings work.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://broadcasts.construct.net/channeleditratingdimension.json
```

Authenticating The Request

This end point is for secret key authenticated requests only. Signed in players cannot call this end point.

secret string Required

Your games secret API key.

Request Parameters

gameID guid Required

The ID of the game you are making this request against. You can find the ID of your game in your Construct Game Services (CGS) account.

thingID guid Required

The ID of the channel the rating dimension exists on that you wish to update.

dimensionID string Required

The ID of the rating dimension you're editing. It is not possible to change the ID's of rating dimensions once created.

title string

A new title for this rating dimension, or omit this parameter to keep existing value. Cannot exceed `128` characters in length.

description string

A new description for this rating dimension, or omit this parameter to keep existing value. Cannot exceed `1024` characters in length.

maxRating uint8

The new maximum allowed rating value, or omit this parameter to keep existing value. `0` is always permitted, so the minimum permitted value is `1` and the maximum permitted value is `255`.

language string

The language this rating dimensions title and description are written in, or omit this parameter to keep existing value. Permitted values are `AR`, `BG`, `CS`, `DA`, `DE`, `EL`, `EN`, `ES`, `ET`, `FI`, `FR`, `HE`, `HU`, `ID`, `IT`, `JA`, `KO`, `LT`, `LV`, `NB`, `NL`, `PL`, `PT`, `RO`, `RU`, `SK`, `SL`, `SV`, `TH`, `TR`, `UK`, `VI`, `ZH`.

requestedLanguage Language Optional

Optionally specify a language for returning translatable properties into this language. If not specified, your games default language will be used.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "dimension": { ... },
  "formattingCulture": "en-us"
}
```

Response Properties

success bool

If the request was successfull or not.

dimension RatingDimension

The returned dimension for the request.

---

formattingCulture string

If some return values are culture specific, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/broadcasts/api-er
  "shouldRetry": false
}
```

Response Properties

---

success bool

If the request was successfull or not.

---

errorMessage string

An error message with more detailed information on why the request failed.

---

helpURL url (string)

A link to documentation which should provide help with the error.

---

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.