UPDATE A BUCKET

View online: https://www.construct.net/en/game-services/manuals/game-services/cloud-save/api-end-points/buckets/edit-bucket

Overview

This end point allows you to update properties on an existing bucket.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://cloudsave.construct.net/editbucket.json
```

Authenticating The Request

This end point is for secret key authenticated requests only. Signed in players cannot call this end point.

secret string Required

Your games secret API key.

Request Parameters

gameID guid Required

The ID of the game you are making this request against. You can find the ID of your game in your Construct Game Services (CGS) account.

bucketID guid Required

The ID of the bucket you wish to edit.

bucketName string

The new name of the game bucket. Omit this parameter to keep the existing name. Cannot exceed `50` characters in length. You must specify at least one of this, `accessMode`, `allowRatings`, `maxBlobSize`, `maxBlobs` or `maxBlobsPerPlayer`.

accessMode string

The new access mode of this bucket (case insensitive). Omit this parameter to keep the existing access mode. Must be one of `Private`, `PublicRead` or `PublicReadWrite`. You must specify at least one of this, `bucketName`, `allowRatings`, `maxBlobSize`, `maxBlobs` or `maxBlobsPerPlayer`.

---

allowRatings bool

If cloud save blobs in this bucket can be rated by players. Omit this parameter to keep the existing setting. You must specify at least one of this, `bucketName`, `accessMode`, `maxBlobSize`, `maxBlobs` or `maxBlobsPerPlayer`.

---

maxBlobSize int32

The maximum size in bytes of cloud save blobs in this bucket. Omit this parameter to keep the existing setting. If a picture is uploaded with a blob, the size of the picture is counted towards this limit as well as the actual cloud save blob size. You must specify at least one of this, `bucketName`, `accessMode`, `allowRatings`, `maxBlobs` or `maxBlobsPerPlayer`.

---

maxBlobs int32

The maximum number of cloud save blobs allowed in this bucket. Omit this parameter to keep the existing name. You must specify at least one of this, `bucketName`, `accessMode`, `allowRatings`, `maxBlobSize` or `maxBlobsPerPlayer`.

---

maxBlobsPerPlayer int16

Optionally specify the maximum number of blobs an individual player can save to this bucket. You must specify at least one of this, `bucketName`, `accessMode`, `allowRatings`, `maxBlobSize` or `maxBlobs`.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "bucket": { ... },
  "formattingCulture": "en-us"
}
```

Response Properties

---

success bool

If the request was successfull or not.

bucket Bucket

The bucket returned from the request.

formattingCulture string

If some return values are culture specific, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/cloud-save/api-er
  "shouldRetry": false
}
```

Response Properties

success bool

If the request was successfull or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.