# GET A BUCKET

**View online:** https://www.construct.net/en/game-services/manuals/game-services/cloud-save/api-end-points/buckets/get-bucket

## Overview

This end point allows you to retrieve an existing bucket.

## Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://cloudsave.construct.net/getbucket.json
```

## Authenticating The Request

No authentication is required for this request type.

## Request Parameters

**gameID guid Required**

The ID of the game you are making this request against. You can find the ID of your game in your Construct Game Services (CGS) account.

**bucketID guid Required**

The ID of the bucket you wish to retrieve.

## Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "bucket": { ... },
  "formattingCulture": "en-us"
}
```

### Response Properties

**success bool**

success bool

If the request was successfull or not.

---

**bucket** Bucket

The bucket returned from the request.

---

**formattingCulture string**

If some return values are culture specific, this property indicates what culture the values have been rendered as.

# Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/cloud-save/api-er
  "shouldRetry": false
}
```

## Response Properties

---

**success** bool

If the request was successfull or not.

---

**errorMessage string**

An error message with more detailed information on why the request failed.

---

**helpURL url (string)**

A link to documentation which should provide help with the error.

---

**shouldRetry** bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.