SET PICTURE

View online: https://www.construct.net/en/game-services/manuals/game-services/cloud-save/api-end-points/cloud-saves/set-picture

Overview

Use this end point to set a picture for a cloud save.

Request URL

All parameters in the request must be sent as a `POST` HTTP request. Make all requests to the following URL:

```
https://cloudsave.construct.net/setpicture.json
```

Authenticating The Request

This end point can be called by signed in players, or with secret key authentication.

Session Key Authentication

sessionKey string Required

The session key of the player you're making the request against.

Secret Key Authentication

secret string Required

Your games secret API key.

Request Parameters

gameID guid Required

The ID of the game you are making this request against. You can find the ID of your game in your Construct Game Services (CGS) account.

blobID guid Required

The ID of the cloud save blob you wish to set a picture for.

picture string Sometimes required

The base64 encoded picture being set. You must specify this, `pictureURL` or `pictureData`.

---

pictureURL url (string) Sometimes required

The absolute URL of the picture being set. You must specify this, `picture` or `pictureData`.

---

requestedLanguage Language Optional

Optionally specify a language for returning translatable properties into this language. If not specified, your games default language will be used.

---

culture string Optional

Optionally specify a supported culture code for rendering various properties. If not specified, the `requestedLanguage` default culture code will be used.

File Data

This request additionally supports the posting of files. These files should be sent as `multipart/form-data,` with the corresponding keys.

---

pictureData multipart/form-data Sometimes required

The data of the picture. You must specify this, `picture` or `pictureURL`.

Success Response

Successful responses always return a `HTTP 200` status code.

```
{
  "success": true,
  "blob": { ... },
  "formattingCulture": "en-us"
}
```

Response Properties

---

success bool

If the request was successfull or not.

---

blob Blob

The blob object returned from the query.

formattingCulture string

If some return values are culture specific, this property indicates what culture the values have been rendered as.

Failure Response

Unsuccessful responses always return `HTTP 4xx` status codes.

```
{
  "success": false,
  "errorMessage": "Your request failed due to...",
  "helpURL": "https://www.construct.net/en/game-services/manuals/game-services/cloud-save/api-er
  "shouldRetry": false
}
```

Response Properties

success bool

If the request was successfull or not.

errorMessage string

An error message with more detailed information on why the request failed.

helpURL url (string)

A link to documentation which should provide help with the error.

shouldRetry bool

Should the client wait a short period of time and retry the request. Usually this is false, but returns true if the request failed due to rate limiting.